

INDUSTRIAL WATER CHILLER

TAEvo-M05 / M10



Product Specifications



| CAPACITIES | | M05 | M10 |
|---|-----|-------|--------|
| Cooling Capacity | ton | 0.51 | 0.99 |
| <i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i> | | | |
| BTU/hr | | 6,012 | 11,904 |
| Tank Volume | gal | 7 | 7 |

| DIMENSIONS | | M05 | M10 |
|------------|-------|------|------|
| Width | 86 in | 22.6 | 22.6 |
| Depth | | 26.3 | 26.3 |
| Height | | 30.9 | 30.9 |
| Weight | lbs | 170 | 184 |

Features / Benefits

- UL & CE listed
- Stocked for quick delivery
- Indoor / Outdoor model
- Closed loop water circulation
- Optimal temperature control
- Condenser coil filters
- Closed expansion kit
- Crankcase heaters

| ELECTRICAL | | M05 | M10 |
|------------|--|-----|-----|
| Volts | | 230 | 230 |
| Phase | | 1 | 1 |
| Hertz | | 60 | 60 |
| FLAmps | | 8.2 | 14 |

Options

- Remote start/stop kit
- Open expansion kit
- Glycol filling kit
- Non ferrous water circuit
- Condenser coil coating
- Low ambient package for colder climates

| MISC SPECS | | M05 | M10 |
|------------------|-----|-------|-------|
| Refrigerant | | R22 | R22 |
| Protection Class | | IP 32 | IP 32 |
| Flow Rate | gpm | - | - |
| Pump Power | kW | 0.33 | 0.33 |
| Fan Power (each) | kW | 0.186 | 0.186 |
| # of Fans | | 1 | 1 |
| Noise Level | dBa | - | - |
| Connection Size | npt | 1/2" | 1/2" |